


Specifications:
 Current Rating: 1.0 Amp
 Contact resistance: 20m Ohm Max
 Insulator resistance: 1000M Ohm min.
 Withstanding Voltage: 500V AC/Minute
 Operating Temperature Range: -40° ~ +105° C
 Material And Finish
 Insulator: Polyester, (PA6T UL94V-0)
 Insulator Color: Black
 Contact: Brass
 Contact Plated: See Contact Plated Tab.

Ordering information



- No. of Rows Pitch: 1
 1. Single 1.08±0.0mm
 2. Double 2.10±1.0mm
- No. of PIN: (2-100P)
 40~40P 1P=10P
 3. 12±1.27mm
 4. 20±2.0mm
 5. 25±2.54mm

Plastic Height: 10±1.0mm
 S: 180
 R: 90
 16±1.0mm
 17±1.7mm
 25±2.54mm

Plastic Packaging:
 Material: 13Bag
 13Pkg 2710kg
 31Pkg 5420kg
 43Pkg 8693kg
 51LPK

Gold Plated	Plating	Shielding	Part No.	Part No.
Special Color	Special Color	Special Color	Special Color	Special Color
Q0	Board Frame	11	Board 1U"	The 1000"
Q1	Board 1U"	11	Board 1U"	The 1000"
Q2	Board 2U"	12	Board 2U"	The 2000"
Q3	Board 3U"	13	Board 3U"	The 3000"
Q4	Board 5U"	14	Board 5U"	The 1000"
Q5	Board 10U"	15	Board 10U"	The 1000"
Q6	Board 15U"	16	Board 15U"	The 1000"
Q7	Board 20U"	17	Board 20U"	The 1000"

Plastic Base

Type	可定制尺寸
H	1.0/1.6/2.0
PA	4.0/2.0
PD	4.0/8.0
PC	2.0/3.0



PCB LAYOUT

未注公差
 UNLESS OTHERWISE
 SPECIFIED TOLERANCE

线性 (LINER)

角度 (ANGLES)

第三视角投影
 THIRD ANGLE
 PROJECTION

品名 (TITLE): PH1.27 1*NIP 180° DIP 双塑 系列图

绘图 (DRAWING) Suzhoujing

审核 (CHECK) Cai Wong

日期 (DATE)



A4

比例 (SCALE) 1:1

单位 (UNIT) MM

页数 (SHEET) 10F1

